

Internal Structure of AJCE Hammers

F series (Outward valve type)

- ✓ **Accumulator** absorbs shocks and fluctuations, improving life-time of hydraulic breakers.
Applicable breakers : from 810M to 1500M, from 180F to 680F.
- ✓ **Valve adjuster** controls the speed and power output of hydraulic breaker.
Applicable breakers : from 600M to 1500M, from 180F to 680F.
- ✓ **ABF(Anti Blank Firing)** system protects main body from idle hammering.
Applicable breakers : all models
- ✓ **Auto greasing system** improves productivity and comfort for operators.
Applicable breakers : from 500M to 1500M, from 180F to 680F.
- ✓ **Long tool pin** and **round nut** increase the life time of front head.
Applicable breakers : all models
- ✓ **On control valve** provides sufficient oil flow into the cylinder.
- ✓ **Air check valve** enables underwater hammering.
Applicable breakers : all models

Advantage of Real Manufacturer



Stable Quality



Competitive Price



Customized OEM



Swift A/S



FACE BOOK



You Tube

M series (Inward valve type)



AJCE KOREA

Add : No.14 Maehwa road 116, Siheung city, Gyeonggi province,
14942, KOREA
Tel : +82 (0)31 315 6454 Fax : +82 (0)31 315 6455
E-mail : info@ajce.co.kr URL : www.ajce.co.kr



AJCE EUROPE

Add : Lindtsedijk 39, 2995 XL Heerjansdam, The Netherlands
Tel : +31 (0)78 737 02 55 Tel : +31 (0)6 14 670 489
E-mail : info@ajce.eu URL : www.ajce.eu

PLEASE CONTACT

The Machine Never Tells a Lie!

AJCE

AJ Construction Equipment Co., Ltd.



About AJCE

AJCE KOREA is the leading manufacturer in construction excavator attachment industry mainly focusing on hydraulic breakers.

Since 1990, the real producer has been supporting with our valuable partners and their customers with quality products and up-right business process.

100% In-House manufacturing with genuine materials has facilitated the development of the most extensive and long-term business partnerships all over the world.

27-year-knowhow and **well-experienced engineers** have enabled **AJCE KOREA** to respond swiftly to various needs and wishes for the worldwide clients.

All AJCE hydraulic hammers are designed, manufactured and assembled by **AJCE**.

History of AJCE

- Feb 1990** Established AJIN PRECISION and started manufacturing control valves for construction equipments.
- Mar 1991** Started producing minor components for hydraulic breakers Such as front cover, thrust bush, through bolt, etc.
- May 1993** Moved to 2nd factory and started manufacturing major components for rock breakers Such as cylinder, front head, piston, etc.
- Sep 1997** Moved to 3rd factory and started assembling and providing OEM
- Feb 2000** Changed to incorporated company, AJ Construction Equipment Co.,Ltd.
- Aug 2006** Developed full line of hydraulic hammers from 1 to 60 tons class
- Jan 2009** Opened AJCE China in Yantai
- Dec 2010** Acquired CE certificate and opened AJCE Europe in Rotterdam, Netherlands
- May 2013** Awarded Promising Export Firm by Business Administration
- Jun 2013** Acquired GOST certificate
- Dec 2013** Awarded USD 5 million Export Tower from KITA, Korea
- Jun 2014** Awarded E-Trade Frontier by Governor of Gyeonggi province
- Aug 2014** Acquired Certificate of Product-Specific Approved Exporter by Customs Service, Korea
- Nov 2015** Acquired Certificate of Designation Small Giant in Export by IBK

ABOUT AJCE & HISTORY OF AJCE





Technical Specification

Description / Model		Inward valve type without Accumulator						Inward valve type with Accumulator										Outward valve type with Accumulator						
		Small Range						Medium Range					Large Range					Medium Range		Large Range				
		100M	200M	300M	350M	400M	430M	450M	500M	600M	710M	810M	1000M	1200M	1250M	1400M	1500M	180F	250F / 280F	350F / 380F	450F	550F / 580F	680F	
Suitable Excavator		ton	0.8~2.5	1.2~3.0	2.5~4.5	3.0~5.5	4~7	6~9	7~14	11~16	15~18	17~22	18~26	25~31	29~35	29~37	35~45	45~55	14~18	18~25	25~35	35~45	45~60	55~70
		lb	1764~5512	2646~6614	7716~9921	6722~12125	8962~15432	13228~19841	15432~30864	24251~35274	33069~39683	37479~48502	39683~57320	55115~68343	63934~77162	63934~81571	77162~99207	99207~121253	30865~39683	39283~55115	55115~77162	72162~99207	99207~132277	121253~154323
Operating Weight	Top Type	kg	90	110	135	210	300	400	540	890	1450	1700	1950	2300	2900	3200	3400	4200	1400	1800	2500	3300	4400	5400
		lb	198	243	298	463	661	882	1190	1962	3197	3748	4299	5071	6393	7055	7496	9259	3086	3968	5512	7275	9700	11905
	Box Type	kg	100	125	150	225	300	400	540	860	1350	1600	1850	2100	2700	2900	3100	3800	1300	1700	2300	3000	4000	4900
		lb	220	276	331	496	661	882	1190	1896	2976	3527	4079	4630	5952	6393	6834	8378	2866	3748	5071	6614	8818	10803
	Side Type	kg	90	110	135	210	300	390	520	800	1400	1650	1900	2200	2800	3000	3200	4000	1350	1750	2400	3100	4100	5000
		lb	198	243	298	463	661	860	1146	1764	3086	3638	4189	4850	6173	6614	7055	8818	2976	3858	5291	6834	9039	11023
Required Oil Flow		l/min	15~30	20~40	25~50	30~60	40~70	50~90	60~100	80~110	90~120	100~150	120~180	150~210	180~240	180~250	200~260	210~290	115~150	125~160	175~220	200~250	210~290	300~400
		gal/min	4.0~8.0	5.3~10.6	6.6~13.2	7.9~16.0	10.6~18.5	13.2~23.8	15.9~26.4	21.1~29.1	23.8~31.7	26.4~39.6	31.7~47.6	39.6~55.5	47.6~63.4	47.5~66.1	50.8~68.7	55.5~76.6	30.4~39.6	33.0~42.3	46.2~58.1	52.8~66.1	55.4~76.6	79.9 ~ 106.5
Setting Pressure		bar	150	150	150	150	170	180	190	200	210	210	210	210	210	210	210	210	210	210	210	210	210	250
		psi	2134	2134	2134	2134	2418	2560	2702	2845	2987	2987	2987	2987	2987	2987	2987	2987	2987	2987	2987	2987	2987	3626
Operating Pressure		bar	90~120	90~120	90~120	100~130	110~140	120~150	130~160	150~170	150~170	160~180	160~180	160~180	160~180	160~180	160~180	160~180	160~180	160~180	160~180	160~180	160~180	190~210
		psi	1280~1707	1280~1707	1280~1707	1422~1849	1565~1991	1707~2134	1849~2276	2134~2418	2134~2418	2276~2560	2276~2560	2276~2560	2276~2560	2276~2560	2276~2560	2276~2560	2276~2560	2276~2560	2276~2560	2276~2560	2276~2560	2755~3045
Impact Energy		joule	203	271	406	542	677	1017	1355	2033	2711	3423	4067	5423	6779	8812	10846	12202	2646	3692	5193	10388	14642	17570
		ft.lbs	150	200	300	400	500	750	1000	1500	2000	2524	3000	4000	5000	6527	8000	9000	1951	2722	3829	7661	10798	12958
		kg.m	21	27	42	56	70	104	139	208	277	350	415	554	692	904	1107	1245	270	377	530	1060	1494	1793
Impact Rate		bpm	800~1400	700~1200	600~1100	500~1000	500~900	400~800	400~800	350~700	350~650	350~600	350~500	300~450	300~450	250~400	250~350	250~350	350~650	350~600	300~450	300~400	250~350	230~320
Hose Diameter		inch	¾, ½	¾, ½	½	½	½	½	¾	¾	1	1	1	1	1¼	1¼	1¼	1¼	1	1	1	1¼	1¼, 1½	1¼, 1½
Noise Level		dB	106	107	109	117	109	115	112	114	115	120	118	120	123	123	124	125	114	120	120	123	126	128
Tool Diameter		mm	40	45	53	60	68	75	85	100	125	135	140	150	155	155	165	175	120	135	150	160	180 / 185	195
		inch	1.6	1.8	2.1	2.4	2.7	3.0	3.4	4.0	4.9	5.3	5.5	5.9	6.1	6.1	6.5	7.0	4.7	5.3	5.9	6.3	7.1 / 7.2	7.7

*The above specifications are subject to change without prior notice for the quality enhancement.

Suitable Excavators

MODEL	TON	DOOSAN / DAEWOO	HYUNDAI	VOLVO	CATERPILLAR	KOMATSU	HITACHI	KOBELCO	CASE	NEW HOLAND	JCB	KUBOTA / HIDROMEK	YANMAR / SUMITOMO	BOBCAT / JOHN DEERE	IHI / LIEBHERR
100M	0.8~2.5	DX7 / DX10	R15 / R16	EC15 / EC20	300.9 / 301.4 / 301.5 301.7 / 302.4	PC05 / PC09 / PC12	ZX08 / ZX10 / ZX14 ZX15 / ZX17	SK09 / SK13 / SK15	CX16 / CX18 / CX20	E9 / E16 / E18	8008 / 8010 / 8014	U-10 / U-17	VI010 / VIO15	S70 / S100 / S130	
200M	1.2~3.0	DX10 / DX15 / DX18 DX27 / DX30 / DX35	R15 / R16 / R22		301.4 / 301.5 / 301.7 302.4 / 303	PC12 / PC15 / PC16 PC18 / PC20 / PC26	ZX14 / ZX15 / ZX17 ZX19 / ZX20 / ZX26	SK13 / SK15 / SK16 SK17 / SK20 / SK25	CX16 / CX18 / CX20 CX22 / CX27	E16 / E18 / E20	8010 / 8014 / 8016 8018 / 8020 / 8025				
300M	2.5~4.5	DX27 / DX30 / DX35	R22 / R28 / R35	EC20 / EC25 ECR28 / M90(SKID)	303 / 303.5 / 304 304.5	PC20 / PC26 / PC27 PC30 / PC35 / PC40	ZX26 / ZX30 / ZX33 ZX35 / ZX38 / ZX40	SK17 / SK20 / SK25 SK27 / SK30 / SK35	CX27 / CX31 / CX35	E20 / E22 / E27 E30 / E35	8018 / 8020 / 8025 8030	U-20	VIO15 / VIO17 / VIO20 VIO27 / VIO30 / VIO35	S150 / S160 / S175 / S185 S205 / S510 / S530 S550 / S570 / S590 17D / 27D / 35D	15NX2 / 20NX2 / 25NX2
350M	3.0~5.5	DX30 / DX35	R35 / R36 / R45 HSL850-7(SKID)	ECR28 / EC30 / EC35 EC38 / M90(SKID)	303 / 303.5 / 304 304.5 / 305 / 305.5	PC30 / PC35 / PC40 PC45	ZX30 / ZX33 / ZX38 ZX40 / ZX40 / ZX48 ZX50	SK27 / SK30 / SK35 SK45 / SK50 / SK55	CX31 / CX35 / CX40 CX50	E30 / E35 / E40	8018 / 8020 / 8025 8030	U-20 / U-30 / KX161-3	VIO20 / VIO27 / VIO30 VIO35	S630 / S650 / S750 S770 / S850 JD250	20NX2 / 25NX2
400M	4~7	DX50 / DX55 / DX60	R45 / R50 / R55	EC35 / EC38 / EC45 EC55 / ECR58 / EW60	304 / 304.5 / 305 305.5 / 307	PC40 / PC45 / PC55 PC60	ZX48 / ZX50 / ZX55 ZX65	SK45 / SK50 / SK55	CX40 / CX50	E40 / E50	3CX / 3CD / 4CX 8040 / 8045 / 8052 8060	U-30 / KX161-3	VIO30 / VIO35 / VIO55	50D / 60D JD315 / JD410	AICHI D600 30NX2 / 35NX2
430M	6~9	DX70 / DX75	R75 / R80	ECR88	307 / 308 415F / 416F / 418F	PC60 / PC75 / PC78	ZX65 / ZX75 / ZX85	SK70 / SK75 / SK80	CX75	E70 / E75 / E80	3CX / 3CD / 4CX JZ70 / 8080	HMK102	VIO55	75D, 80D	
450M	7~14	DX70 / DX75 / DX80		ECR88	308 / 311 / 312 / 313 420F / 430F	PC75 / PC88 / PC100 PC100 / PC120 / PC138	ZX75 / ZX85 / ZX120 ZX130 / ZX135	SK70 / SK75 / SK80 SK100 / SK140	CX80 / WX95				VIO75 / VIO100	85D	
500M	11~16	DX130 / DX140 / DX155	R110 / R130 / R140 R150	EC130 / EC140 / EW145 EC150	311 / 312 / 313 315 / 316	PC120 / PC138	ZX120 / ZX130 / ZX135 ZX160	SK115 / SK135 / SK140	WX125 / CX130 / CX135 WX145	E115 / E135 / E145	JS115 / JS130 / JS140 JS145	HMK140	VIO100 SH130	120C / 135D	A312 / A314
600M	15~18	DX160 / DX170 / DX180	R160 / R170 / R180	EC160 / EW170 / EC180	315 / 316 / 317 318	PC170	ZX160 / ZX170	SK / SK160 / SK170	CX160 / WX165 / CX180 WX185	E150 / EW160 / E170 E175	JS160 / JS175 / JS180		SH160	160C / 190D	A316 / A900 / A912 R914
710M	17~22	DX190 / DX200 / DX210	R170 / R180 / R200 R210 / R220	EW170 / EW180 / EW200 EC210	317 / 318 / 320	PC170 / PC200 / PC210 PC215	ZX170 / ZX190 / ZX200 ZX210	ED195 / SK200 / SK210 SK215 / SK220	CX180 / CX185 / CX210	E195 / E200	JS180 / JS190 / JS200 JS210 / JS220	HMK200 / HMK220	SH200 / SH210	210C	R918 / R920 / R922
810M	18~26	DX200 / DX210 / DX220 DX225 / DX250	R200 / R210 / R220 R250	EW200 / EC210 / ECR235 EC240	320 / 321 / 323 324 / 325 / 326	PC200 / PC210 / PC215 PC228 / PC230 / PC240	ZX200 / ZX210 / ZX225 ZX240 / ZX250	SK200 / SK210 / SK215 SK220 / SK230 / SK235	CX210 / CX225 / CX230 WX240 / CX250	E215 / E220 / E225 E235 / E245	JS230 / JS235 / JS240 JS260			210C / 225C / 230C 240D	R918 / R920 / R922 R924 / R926
1000M	25~31	DX250 / DX255 / DX280 DX290 / DX300	R250 / R290 / R300 R305	EC240 / EC290	324 / 325 / 326 330	PC290 / PC300	ZX250 / ZX280 / ZX300	SK250 / SK260 / SK295	CX250 / CX290	E265 / E305	JS260 / JS290 / JS300	HMK300	SH300	270D	R926
1200M	29~35	DX290 / DX300 / DX320 DX330 / DX340	R280 / R290 / R300 R305 / R320	EC290 / EC305 / EC330	330 / 335	PC290 / PC300 / PC330	ZX300 / ZX330 / ZX350	SK295 / SK330 / SK350	CX290 / CX330 / CX350	E305 / E335	JS290 / JS300 / JS330		SH300 / SH330 / SH350	330C / 350D	R934 / R936
1250M	29~37	DX290 / DX320 / DX330 DX330 / DX340 / DX360	R290 / R300 / R305 R320 / R360	EC290 / EC305 / EC330 EC360	330 / 335 / 336	PC300 / PC330 / PC360	ZX300 / ZX330 / ZX350								
1400M	35~45	DX320 / DX330 / DX340 DX360 / DX370 / DX400 DX420 / DX450 / DX470	R300 / R320 / R360 R380 / R450	EC360 / EC380 / EC460	336 / 345	PC360 / PC390 / PC400	ZX350 / ZX400 / ZX450	SK330 / SK350 / SK400	CX330 / CX350	E335 / E385	JS330 / JS370	HMK370	SH350 / SH450 / SH460	330C / 350D / 370C	R936 / R944 / R946
1500M	45~55	DX400 / DX420 / DX450 DX470 / DX480 / DX500	R450 / R470 / R480 R500 / R520	EC460 / EC480	345 / 349 / 350 352	PC450 / PC490 / PC500	ZX450 / ZX470 / ZX470 ZX520	SK400 / SK480 / SK500	CX490	E385 / E485	JS460		SH450 / SH460 / SH480 SH500	450C	R946 / R950 / R956
180F	14~18	DX140 / DX155 / DX160 DX170 / DX180	R140 / R150 / R160 R170 / R180	EC140 / EW145 / EC150 EC160 / EC170 / EC180	314 / 315 / 316 317 / 318	PC150 / PC160 / PW170 PC180	ZX145 / ZX160 / ZX170	SK140 / SK150 / SK160 SK170	CX145 / CX160 / WX165 CX180	E145 / E150 / EW160 E170 / E175	JS140 / JS145 / JS160 JS175 / JS180	HMK140	SH160	160C	A316 / A900 / A912
250F	18~25	DX180 / DX190 / DX200 DX210 / DX220 / DX225 DX250	R180 / R200 / R210 R220 / R250	EW180 / EW200 / EC210 ECR235 / EC240	318 / 320 / 321 322 / 323 / 324 / 325	PC180 / PC200 / PC210 PC220 / PC228 / PC230 PC240	ZX190 / ZX200 / ZX210 ZX225 / ZX240 / ZX250	ED195 / SK200 / SK210 SK220 / SK230 / SK235	CX180 / CX185 / CX210 CX225 / CX230 / WX240	E195 / E200 / E215 E220 / E225 / E235	JS180 / JS190 / JS200 JS210 / JS220 / JS230 JS235 / JS240	HMK200 / HMK220	SH200 / SH210	190D / 210C / 225C 230C / 240D	R918 / R920 / R922 R924
280F															
350F	25~35	DX250 / DX255 / DX280 DX290 / DX300 / DX320	R250 / R290 / R300 R305 / R320	EC290 / EC305 / EC330	325 / 329 / 330	PC270 / PC290 / PC300 PC308 / PC330	ZX250 / ZX280 / ZX300 ZX330 / ZX350	SK250 / SK260 / SK295 SK330	WX240 / CX290 / CX330	E265 / E305	JS260 / JS290 / JS300 JS330	HMK300	SH300	270D	R926 / R934
380F															
450F	35~45	DX330 / DX340 / DX360 DX370 / DX400 / DX420 DX450 / DX470	R360 / R380 / R430 R450	EC360 / EC380 / EC460	330 / 336 / 345	PC330 / PC340 / PC350 PC400 / PC450	ZX350 / ZX400 / ZX450	SK330 / SK350 / SK400	CX330 / CX350	E335 / E385	JS370 / JS460	HMK370	SH330 / SH350 / SH450 SH460	330C / 350D / 370C 450C	R936 / R944 / R946
550F	45~60	DX450 / DX470 DX500 / DX530	R450 / R450 / R470 R480 / R520	EC460 / EC480	345 / 349 / 350 352	PC450 / PC490 / PC500	ZX450 / ZX470 / ZX490 ZX520	SK480 / SK500	CX490				SH450 / SH460 / SH480 SH500	R946 / R950 / R956 R960	R956 / R960 / R966 R970
580F															
680F	55~70			EC700	352 / 374	PC650	ZX650 / ZX670						SH700		

* B, C, D, W, LC, etc and dash numbers are omitted on above table.

* Suitable hydraulic breaker is to be chosen well according to excavator and job condition, which is largely related to its power and performance.

AJCE Breaker Functions

Functions	100M	200M	300M	350M	400M	430M	450M	500M	600M	710M	810M	1000M	1200M	1250M	1400M	1500M
Box / Side / Top Bracket	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●
Skid Steer Loader Bracket	●	●	●	●	●	●										
Bakhoe Loader Bracket				●	●	●										
Vibration Absorbtion Accumulator											●	●	●	●	●	●
Underwater Hammering Channel	●	●	●	●	●	●		●	●	●	●	●	●	●	●	●
Auto Greasing Channel								●	●	●	●	●	●	●	●	●
Speed Control by Valve Adjuster									●	●	●	●	●	●	●	●
Power Control by Cylinder Adjuster																
Anti Blank Firing System											●	●	●			
Round Nut for Box Bracket									●	●	●	●	●	●	●	●

Chisel Choice

	Chisel type	Working Site
Moil		All demolition work, Road constructionoin, Bridge foundation
Wedge		All demolition work, Trenching rocks, Cutting concrete
Blunt		Mining, Quarrying, Crushing rocks
Cone		Quarrying rocks, Cracking concrete

